

SMALL AND MEDIUM HYDRAULIC BREAKERS

A UNIT FOR EVERY NEED

PERFORMANCE COUNTS



- A** Standard frame with pin and bush connection (F1-F5)
- B** Standard frame for top bracket mounting (F1 – F6)
- C** Low Noise (LN) for top bracket mounting (F2 – F100)
- D** Special BHL frame for backhoe loader mounting (F6)

			F1	F2	F3	F4	F5	F6	F9
Operating weight, standard ¹⁾	kg		66	86	129	172	225	365	
Operating weight, LN ¹⁾	kg			117	160	227	292	350	535
Height with rod, standard	mm		979	1095	1255	1335	1488		
Height with rod, BHL	mm							1641	1750
Height with rod, LN	mm			1050	1159	1255	1369	1400	1595
Operating pressure	min	bar	100	100	100	100	100	100	120
	max		140	140	140	140	140	160	170
Oil flow	min	l/min	9	14	22	28	38	50	45
	max		20	32	42	50	65	150	150
Impact rate	min	bpm	900	900	850	750	700	650	400
	max		1250	1200	1200	1000	900	1600	1400
Impact energy	max	joules	160	260	345	490	710	884	1305
Rod diameter ø	mm		36	45	52	60	68	75	90
Hose inner dia. ø HD, ND	mm		9	12	12	12	12	12	19
Base machine weight	ton		0,5-1,5	1-2,5	1,5-4	2-5	3-7	3,5-10	6-12

¹⁾ Operating weight with top bracket