

FRD DEMOLITION AND SORTING GRAB - FSG TYPE -

Designed to demolish brick walls, and sort and load all kinds of demolished materials. Closed shells. With integrated load-holding valve.



		FSG10-PL	FSG20-PL	FSG30-PL	FSG40-PL	FSG50-PL	FSG60-PL
Weight without adapter plate	kg	200	460	830	1475	1530	1860
Capacity	l	80	200	370	650	720	900
Height open	mm	720	890	1070	1390	1390	1470
Height closed	mm	820	1010	1200	1595	1600	1720
Length closed	mm	650	940	1170	1430	1430	1420
Length open	mm	1110	1620	1920	2225	2235	2340
Width	mm	400	600	800	900	1000	1100
Excavator weight class	t	1-5	5-9	9-15	16-22	23-30	31-45
Top bracket mounting dimensions		Adaptor plate		F35LN	F35LN	F45LN	

FRD DEMOLITION AND SORTING GRAB - FDG TYPE -

Designed for variable use and handling of mixed materials such as construction waste and recycling materials. Open jaws of Hardox 400 to ensure long lifetime. With integrated load-holding valve.



		FDG10-PL	FDG20-PL	FDG30-PL	FDG35-PL	FDG40-PL	FDG50-PL	FDG60-PL
Weight without adapter plate	kg	220	510	900	940	1590	1830	2170
Capacity	l	80	200	370	370	650	760	925
Height open	mm	720	890	1070	1200	1450	1490	1600
Height closed	mm	820	1010	1200	1350	1600	1710	1800
Length closed	mm	650	940	1170	1170	1410	1450	1530
Length open	mm	1110	1620	1920	1920	2260	2260	2500
Width	mm	400	600	800	800	900	1000	1230
Excavator weight class	t	1-5	5-9	9-15	15-20	16-22	23-30	29-45
Top bracket mounting dimensions		Adaptor plate		F35LN	F35LN	F35LN	F45LN	

FRD DEMOLITION AND SORTING GRAB - FMP TYPE -

Multipurpose grab for stone laying, sorting and handling of construction and recycling materials, rough bulk and horticultural materials. Closed shells with Esco bucket teeth for a solid grip. With integrated load-holding valve.



		FMP10-PL	FMP20-PL	FMP30-PL	FMP40-PL	FMP50-PL	FMP60-PL
Weight without adapter pl.	kg	195	450	800	1410	1570	2170
Capacity	l	50	120	270	480	570	920
Height open	mm	720	1000	1210	1560	1560	1735
Height closed	mm	695	960	1200	1580	1580	1900
Length closed	mm	610	900	1145	1360	1360	1510
Length open	mm	970	1400	1790	2055	2055	2500
Width	mm	400	500	660	790	950	1000
Excavator weight class	t	1-5	5-9	9-15	16-22	23-30	30-40
Top bracket mounting dimensions		Adaptor plate		F35LN	F35LN	F45LN	