

# WHERE EXPERIENCE

## FRD PRIMARY CRUSHER - VP TYPE -

To demolish concrete constructions/buildings and to cut reinforcing steel bars. Two cylinder design means maximum opening width for its size. The cast steel frame and Hardox steel arms offer optimum crushing performance with minimum wear.

		VP15 FT	VP22 FT
Operating weight <sup>1)</sup>	kg	1660	2700
Opening width	mm	820	1100
Crushing force, front	t	54	80
Crushing force, middle	t	70	105
Cutting force	t	180	282
Cutter length	mm	155	210
Base machine weight	t	15-20	20-30
Acceleration valve		yes	yes
360° rotation		hydraulic	hydraulic

<sup>1)</sup> Operating weight without top bracket

## FRD MULTI-PURPOSE CRUSHER - VM TYPE -

For applications such as low noise crushing of concrete, brick, asphalt and similar materials. With extra long cutters.

		VM15 FT	VM22 FT
Operating weight <sup>1)</sup>	kg	1320	2040
Opening width	mm	680	920
Crushing force, front	t	42	51
Crushing force, middle	t	65	78
Cutting force	t	152	180
Cutter length	mm	160	360
Base machine weight	t	13-20	19-25
Acceleration valve		yes	yes
360° rotation		hydraulic	hydraulic

<sup>1)</sup> Operating weight without top bracket

