

# WHEEL LOADER.

## 1. Highly efficient

Automatic idle returns the engine to 700rpm after 30 seconds of inactivity.

## 2. Maximum protection

Full width counterweight\* protects bonnet and cooling pack from damage.

## 3. Giving great service

Widewire radiators and optional reversing fan boost cooling efficiency in arduous environments.

## 6. Armed and ready

Choice of loader arm length and configuration for total versatility.

## 5. Well protected

ROPS and FOPS cabs are positively pressurised to minimise dust and increase operator comfort and safety.

## 4. DPF free

Meets emission regulations without needing a DPF; reduces costs, downtime and the fire risks associated with regeneration.

\*Machine dependent





Proportional auxiliary hydraulic flow provides great versatility for attachment use.



Optional auto lubrication kit takes care of machine greasing requirements.



JCB Smoothride load suspension limits shock loadings, reducing material spillage.



Rear lights are safely recessed and protected by the solid counterweight.



JCB Command Plus cab has two LCD screens for easy access to operating menus. Adjustable steering column with seat mounted hydraulic controls.

		437 HT	457 HT
Maximum gross engine power	kW (hp)	136 (183)	193 (258)
Maximum operating weight range	kg	14780 - 16103	20152 - 22255
Shovel capacity	m <sup>3</sup>	2.3 - 2.7	3.1 - 3.5
Full turn tipping load range	kg	5493 - 9851	7982 - 14719
Payload range	kg	2746 - 4926	3911 - 7359
Maximum breakout force	kN	153	175
Load over height	m	37.5 - 4.98	3.99 - 4.99